# LEGACY MODEL - 48" DUAL FUEL RANGE - 4 BURNERS, INFRARED CHARBROILER AND INFRARED GRIDDLE

## **DF484CG**

#### **FEATURES**

Cook at higher highs and lower lows with four dual-stacked, sealed burners that produce up to 20,000 Btu and deliver as low as 300 Btu

Rely on a 16,000 Btu infrared charbroiler for more succulent steaks, chops, and burgers

Rely on a 15,000 Btu infrared griddle to sear burgers, stir-fry vegetables, and more

Clean up sloshes and spills easily with the seamless, sealed, black porcelain-coated burner pans

Assures predictably delicious results with a variety of modes including Convection Roast, Proof, and Dehydrate

Operate easily with a control panel that rotates out of sight when not in use

Control heat and airflow expertly as dual convection creates just the right cooking environment for everything from Cornish hens to cherry pie to butternut squash

Leave nothing to chance. Our temperature probe alerts you when your dish has reached the desired temperature for worry-free, delicious results

Includes options such as self-clean, delayed start, timed cook, Sabbath mode, and more

Re-ignites flame automatically with our spark ignition system for improved temperature control and added safety

Move pots and pans effortlessly across the continuous cast-iron grates

Find your kitchen style with a choice of iconic red, black, or brushed stainless control knobs

See food clearly with bright interior halogen lights and large double-panel glass door windows

## ACCESSORIES

#### 11" Cutting Board

18" Broiler Pan

18" Dehydration Kit

18" Full-Extension Oven Rack

18" Standard Oven Racks

2-Burner Wok Grate

3 1/4" Front Leg Covers

3 1/4" Rear Caster Covers

3 3/4" (95) Front Leg Covers

3 3/4" Rear Caster Covers

30" Bake Stone Kit

30" Broiler Pan and Rack

30" Full-Extension Ball-Bearing Oven Rack

4 1/4" Front Leg Covers

4 1/4" Rear Caster Covers

4 3/4" Front Leg Covers




MOLF

## KNOB OPTIONS



## **TOP CONFIGURATION**



#### **RANGETOP SPECIFICATIONS**

- 1 9,200 Btu burner
- 1 20,000 Btu burner
- · Stainless-steel island trim
- 1 15,000 Btu burner
- 1 18,000 Btu burner
- 1 16,000 Btu charbroiler
- 1 15,000 Btu griddle
- · Stainless-steel charbroiler and griddle covers

4 3/4" Rear Caster Covers
48" Stainless Steel Kickplate
48" and 60" Black Knobs
48" and 60" Red Knobs
48" and 60" Stainless Steel Knobs
Dehydration Kit
Filler Trim
Griddle Cleaning Kit
Griddle Cleaning Pads
Griddle Cleaning Solution
Oven Rack Set (3)
Premier Baking Sheet
Temperature Probe
Brushed stainless, brass or chrome bezels
5" and 10" stainless steel risers, and 20" riser with shelf
Accessories available through an authorized dealer. For local dealer information, visit <u>subzero-wolf.com/locator</u> .

Specifications are subject to change without notice. This information was generated on June 13, 2025. Verify specifications prior to finalizing your cabinetry/enclosures.


# LEGACY MODEL - 48" DUAL FUEL RANGE - 4 BURNERS, INFRARED CHARBROILER AND INFRARED GRIDDLE

# **PRODUCT SPECIFICATIONS**

Model	DF484CG
Dimensions	47 7/8"W x 36 7/8"H x 29 1/2"D
Oven 1 Interior Dimensions	14"W x 16 1/2"H x 19"D
Oven 2 Interior Dimensions	25"W x 16 1/2"H x 19"D
Oven 1 Usable Capacity	1.5 cu. ft.
Oven 1 Overall Capacity	2.5 cu. ft.
Oven 2 Usable Capacity	2.8 cu. ft.
Oven 2 Overall Capacity	4.5 cu. ft.
Door Clearance	19 1/2"
Electrical Supply	240/208 VAC, 60 Hz
Electrical Service	50 amp dedicated circuit
Gas Supply	3/4" ID line
Gas Inlet	1/2" NPT female


# ELECTRICAL

GAS




NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

# DIMENSIONS



MOLF

# STANDARD INSTALLATION



\*Without ventilation hood, 36" (914) minimum clearance countertop to combustible materials, 44" (118) for charbroiler. NOTE: Shaded area above countertop indicates minimum clearance to combustible surfaces,

combustible materials cannot be located within this area.

For island installation, 12" (305) minimum clearance back of range to combustible rear wall above countertop.