

PWC482418

FEATURES

- Heavy-duty stainless steel construction

- Handfinished with hemmed edges and welded seams

- Blower required (internal, in-line or remote blowers available)

- Recessed controls for sleeker look

- Infinite speed blower control

- Bright halogen lighting

- Heat sentry for safety

- Transition with backdraft minimizes backward flow of cold air

- Install with accessory duct cover for chimney-style hood

- Rigorously tested in our U.S. manufacturing facilities for decades of use

- Exceptional 24/7 support from our Customer Care team in Madison

ACCESSORIES

- Backsplash

- Backsplash with Warming Racks

- Make-Up Air Damper

- 38" high stainless steel backsplash with or without warming racks

- Make-up air damper

- Inline Blowers

- Internal Blowers

- Remote Blowers

- Pro Chimney Hood Duct Covers

Accessories available through an authorized dealer.
For local dealer information, visit subzero-wolf.com/locator.




BLOWER OPTIONS

- 300 CFM Internal
- 450 CFM Internal
- 600 CFM Internal
- 900 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote

PRODUCT SPECIFICATIONS

Model	PWC482418
Dimensions	48"W x 18"H x 24"D
Weight	94 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

ELECTRICAL



NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

DIMENSIONS

