# 30" M SERIES PROFESSIONAL CONVECTION STEAM OVEN - PLUMBED

**CSOP3050PM/S/P**

## FEATURES

- The elegant, modern aesthetic pairs perfectly with a full suite of similarly styled Sub-Zero, Wolf, and Cove appliances
- Full-color touchscreen simplifies use
- The door opens and closes quietly for an elevated experience
- Save up to 50 personalized recipe presets for quick access to your favorite go-to meals
- Cooking modes include Steam, Convection, Broil, Slow Roast
- Oven features a 1750-watt recessed broil element with multiple settings
- 2.4 cubic-foot oven cavity allows multiple dishes to be placed side by side at once
- 1889-watt dual convection system ensures even, multi-rack baking and consistent results
- Three full-extension rack positions and one standard position allow easy access and increased cooking flexibility
- Plumbed water supply provides continuous steam cooking
- The temperature probe alerts you when your dish has reached the desired temperature

## ACCESSORIES

- Broiler Rack
- Descaling Solution
- Enameled Broiler Pan
- Perforated Pan - 12 3/4" x 1 1/2" x 7"
- Perforated Pan - 24 3/4" x 1 1/8" x 14 5/8"
- Solid Pan - 12 3/4" x 1 1/2" x 7"
- Solid Pan - 24 3/4" x 1 1/8" x 14 5/8"
- Standard Oven Rack
- Temperature Probe

Accessories available through an authorized dealer.
For local dealer information, visit subzero-wolf.com/locator.

Specifications are subject to change without notice. This information was generated on October 10, 2026. Verify specifications prior to finalizing your cabinetry/enclosures.

# 30" M SERIES PROFESSIONAL CONVECTION STEAM OVEN - PLUMBED

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| Model | CSOP3050PM/S/P |
| Dimensions | 29 7/8"W x 17 7/8"H x 22 1/2"D |
| Oven Interior Dimensions | 25 1/4"W x 10 3/4"H x 15 1/8"D |
| Overall Capacity | 2.4 cu. ft. |
| Usable Capacity | 1.8 cu. ft. |
| Door Clearance | 14 3/16" |
| Weight | 91 lbs |
| Electrical Supply | 240/208 VAC, 60 Hz |
| Electrical Service | 20 amp dedicated circuit |
| Drain Line TestSpec | 10' (3 m) corrugated drain tubing |
| Plumbing Supply | 6.5' (2 m) braided tubing with 3/8" female compression fitting |
| Plumbing Pressure | 15–145 psi |
| Conduit Length | 4 Feet |

## ELECTRICAL




## PLUMBING




**NOTE:** Dimensions in parenthesis are in millimeters unless otherwise specified

## DIMENSIONS




## FLUSH INSTALLATION




**Will be visible and should be finished to match cabinetry.*
***Dimension provides minimum reveals.*

*NOTE: Location of electrical supply within opening may require additional cabinet depth.*